



## LZM-Z SERIES PANEL MOUNTING **ROTAMETERS WITH FLOW CONTROL**

## STANDARD FEATURES:

- **BUILT IN STAINLESS STEEL FLOW** CONTROL VALVE
- CONSTRUCTED OF STAINLESS STEEL, ACRYLIC & ABS
- **DUAL SCALES IN LITRES & GALLONS** PER MINUTE
- MAXIMUM WORKING PRESSURE 10 BAR
- MAXIMUM TEMPERATURE 60°C
- **BSP PIPE THREADS**
- SUITABLE FOR WATER & COMPATIBLE LIQUIDS WITH AN SG OF 1
- 12 MONTH WARRANTY\*



## MODEL:

Model	Flow Rate	Dimensions	Connections
LZM-15ZT-4	0.5 to 4 LPM	175 x 35 x 40mm ( h x w x d)	1/2+BSP
LZM-15ZT-7	0.7 to 7 LPM	175 x 35 x 40mm ( h x w x d)	1/2+BSP
LZM-15ZT-11	1 to 11 LPM	175 x 35 x 40mm ( h x w x d)	1/2+BSP
LZM15-ZT-18	2 to 18 LPM	175 x 35 x 40mm ( h x w x d)	1/2+BSP
LZM25-ZT-60	6 to 60 LPM	234 x 45 x 46mm (h x w x d)	1+BSP
LZM25-ZT-170	17 to 170 LPM	234 x 45 x 46mm (h x w x d)	1+BSP

## **OPTIONS:**

Smaller and larger sizes, alternative flow ranges and alternative materials, are available on request.

☑PO Box 300-596, Albany, Auckland 0752, New Zealand 281 1865

■sales@aquasales.co.nz

<sup>\*</sup> Please refer to Aqua Products Limitedgterms and conditions of sale for complete warranty conditions.