

LZS SERIES PLASTIC TUBE FLOW METERS

STANDARD FEATURES:

- TAPERED TUBE IS CHEMICAL RESISTANT AS PLASTIC
- FLOAT IS ABS
- GUIDE IS 316SS (PTFE ON REQUEST)
- END CONNECTIONS ARE PVC (ABS ON REQUEST)
- UNION CONNECTIONS FOR EASY DISASSEMBLY / CLEANING
- ACCURACY $\pm 4\%$
- TEMPERATURE RANGE 0-60°C
- PRESSURE (MAX) 6 BAR
- 12 MONTH WARRANTY*



MODEL:

Model	Flow Rate	Nominal Diameter	Height	Connections
LZS-15D-50	5-50LPH	15mm	202mm	1/2+BSP
LZS-15D-100	10-100LPH	15mm	202mm	1/2+BSP
LZS-15D-250	25-250LPH	15mm	202mm	1/2+BSP
LZS-15D-500	50-500LPH	15mm	202mm	1/2+BSP
LZS-15D-1000	100-1000LPH	15mm	202mm	1/2+BSP
LZS-25D-1000	4-40 LPM	25mm	226mm	3/4+BSP
LZS-25D-1600	160-1600 LPH	25mm	226mm	3/4+BSP
LZS-25D-2500	250-2500LPH	25mm	226mm	3/4+BSP
LZS-32D-6	0.6-6 m3/hr	32mm	288mm	1+BSP
LZS-50D-16	1.6-16 m3/hr	50mm	341mm	1 1/2+BSP
LZS-65D-40	4-40 m3/hr	65mm	430mm	2+ BSP
LZS-65D-60	6-60 m3/hr	65mm	430mm	2+BSP
LZS-100D-120	12-120 m3/hr	100mm	550mm	Flange

OPTIONS:

D=short type with float guide. Also available in long version without guide.

Available with flange connections.

Body available in polysulphone, fittings available in PVC, floats available in SS for higher temperatures. Available up to DN150 and flowrates to 200m3/hr.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

LZS SERIES PLASTIC TUBE FLOW METERS WITH LIMIT SWITCH

STANDARD FEATURES:

- TAPERED TUBE IS CHEMICAL RESISTANT AS PLASTIC
- FLOAT IS ABS
- GUIDE IS 316SS (PTFE ON REQUEST)
- END CONNECTIONS ARE PVC (ABS ON REQUEST)
- UNION CONNECTIONS FOR EASY DISASSEMBLY / CLEANING
- ACCURACY $\pm 4\%$
- TEMPERATURE RANGE 0-60°C
- PRESSURE (MAX) 6 BAR
- 12 MONTH WARRANTY*



MODEL:

Model	Flow Rate	Nominal Diameter	Height	Connections
LZS-15D-50 SW	5-50 LPH	15mm	202mm	1/2+BSP
LZS-15D-100 SW	10-100 LPH	15mm	202mm	1/2+BSP
LZS-15D-250 SW	25-250 LPH	15mm	202mm	1/2+BSP
LZS-15D-500 SW	50-500 LPH	15mm	202mm	1/2+BSP
LZS-15D-1000 SW	100-1000 LPH	15mm	202mm	1/2+BSP
LZS-25D-1000 SW	100-1000 LPH	25mm	226mm	3/4+BSP
LZS-25-1600 SW	160-1600 LPH	25mm	226mm	3/4+BSP
LZS-25-2500 SW	250-2500 LPH	25mm	226mm	3/4+BSP
LZS50D-16 SW	1.6-16 m ³ /hr	50mm	341mm	1 1/2+BSP

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.