

PH SENSORS



PH ELECTRODE MODEL - EPH

Description	Single junction epoxy shaft pH electrode (pH 0-14). Max pressure 7 bar at 70 °C. 12mm dia. Minimum conductivity 100µS.
Applications	Potable water, swimming pools, laboratory use.
EPHS	With 0.8 meter cable and BNC connector.
EPHM	With 4.5 meter cable and BNC connector.
EPHL	With 15 meter cable and BNC connector.



PH ELECTRODE MODEL - EPHM/D

Description	Double junction epoxy shaft pH electrode (pH 0-14). Max pressure 7 bar at 70°C. 12mm dia. Minimum conductivity 1 µS.
Applications	As above plus wastewater e.g. electroplating, and medias containing proteins, silver or sulphides. Also suitable for high purity water.
EPHM/D	With 4.5 meter cable and BNC connector.



PH ELECTRODE MODEL - EPHMD/100

Description	Double junction epoxy shaft pH electrode (0-14 pH) Max pressure 7 bar at 100°C, 12mm dia. Minimum 100uS.
Applications	Wastewater e.g. electroplating, and medias containing proteins, silver or sulphides. Suitable for high temperature wastewater applications.
EPHMD/100	With 4.5 metre cable with BNC connector.



PH ELECTRODE MODEL - EPHM/HF

Description	Double junction epoxy shaft pH electrode (0-14 pH) with 12mm dia. Minimum 100uS. 7 bar/Max 70°C.
Applications	Hydrogen fluoride resistant.
EPHM/HF	4.5 m cable and BNC connector.



PH ELECTRODE MODEL - EPHSC

Description	Epoxy shaft pH electrode (0-14 pH) with flat end and self cleaning action. Max pressure 7 bar at 70°C. 12mm dia. Minimum 100µS.
Applications	High solids wastewater, mount in flow path for self cleaning action.
EPHSC	With 4.5 meter cable and BNC connector.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

PH SENSORS



PH ELECTRODE MODEL - EPHSN6, EPHM/D/SN6, EPHSC/SN6

Description	Epoxy shaft pH electrode (0-14 pH) with PG13.5 mounting thread and SN6 connector.
EPHSN6	7 bar 70°C, Min conductivity 100 µS.
EPHM/D/SN6	Double junction, 7 bar 70°C, Min conductivity 1 µS.
EPHSC/SN6	7 bar 70°C, Min conductivity 100 µS, self cleaning (flat tip).

ACCESSORIES FOR ORP AND PH PROBES INSTALLATIONS

CASN6S	BNC/SN6 cable for ERHSN6 probe. 5m.
CASN6M	BNC/SN6 cable for ERHSN6 probe. 10m.
CASN6L	BNC/SN6 cable for ERHSN6 probe. 15m.
GHIERA	PG13.5 threading nut for ORP probes, with O-ring.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.