

DELTA ESCALDA WATER SOFTENER

The Amazing Escalda water softener sets a new standard for efficiency and performance.

STANDARD FEATURES:

- ULTRA COMPACT
- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



DIMENSIONS:

240mm (W) x 540mm (L) x 483mm (H)

Small enough to fit under a sink bench, the Delta Escalda can soften up to 1500 litres per hour of water. Regenerating automatically as required, the Escalda regenerates in just 15 minutes, using only 18 litres of water and 0.3kgs of salt. The softener sits inside the brine tank for a compact tidy finish.

APPLICATIONS:

Domestic use, cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
ESCALDA 3L LR	150ppm/m3	50-200ppm Hardness
ESCALDA 3L	150ppm/m3	150-600ppm Hardness

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA TIBERA WATER SOFTENER

Two water softeners in one tidy package. The Tibera Duplex Softener with duty/standby operation provides continuous uninterrupted soft water.

STANDARD FEATURES:

- ULTRA COMPACT
- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- CONTINUOUS UNINTERRUPTED SOFT WATER
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



DIMENSIONS:

522mm (W) x 518mm (L) x 468mm (H)

The Tibera has two 3.3L water softeners mounted inside a brine tank. The Tibera can soften up to 1500 litres per hour of water. Regenerating automatically as required, each softener regenerates in just 15 minutes, using only 18 litres of water and 0.3kgs of salt. Two softeners sit inside one brine tank for a compact tidy finish.

APPLICATIONS:

Domestic use, Cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
TIBERA 3.3L LR	2x150ppm/m3	50-200ppm Hardness
TIBERA 3.3L	2x150ppm/m3	150-600ppm Hardness

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA ONEGA WATER SOFTENER

The Delta Onega water softener provides a higher capacity option, with the same controller design for high performance and efficiency.

STANDARD FEATURES:

- COMPACT
- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



DIMENSIONS:

276mm (W) x 553mm (L) x 552mm (H)

The Delta Onega can soften up to 2000 litres per hour of water. Regenerating automatically as required, the Onega regenerates in just 24 minutes, using 40 litres of water and 0.9kgs of salt. The softener sits inside the brine tank.

APPLICATIONS:

Domestic use, Cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
ONEGA 1x9L	450ppm/m3	200-600ppm Hardness

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA ONEGA DUPLEX WATER SOFTENER

The Delta Onega Duplex water softener provides high capacities and continuous soft water, in a compact format.

STANDARD FEATURES:

- COMPACT
- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- CONTINUOUS UNINTERRUPTED SOFT WATER
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



DIMENSIONS:

552mm (W) x 553mm (L) x 552mm (H)



The Delta Onega Duplex also softens up to 2000 litres per hour of water. For high capacity and continuous soft water, a duty/standby configuration is recommended. Regenerating automatically as required, the Onega regenerates in just 24 minutes, using 40 litres of water and 0.9kgs of salt. Two softeners sit inside a single container with matching brine tank.

APPLICATIONS:

Domestic use, Cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
ONEGA 2x9L	2 x 450ppm/m3	200-600ppm Hardness

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA ONTARIO WATER SOFTENER

The Delta Ontario water softener provides the highest capacity option in the Delta range.

STANDARD FEATURES:

- COMPACT
- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



The Delta Ontario is the largest softener in the Delta range. It can soften up to 2000 litres per hour of water. Regenerating automatically as required, the Ontario uses only 100 litres of water and 1.2kgs of salt. The softener sits inside the brine tank for a compact tidy finish.

APPLICATIONS:

Domestic use, Cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
ONTARIO 12L	600ppm/m3	200-600ppm Hardness

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA ONTARIO DUPLEX WATER SOFTENER

Larger capacity 12 Litre water Softener. The Duplex version has separate brine tank.

STANDARD FEATURES:

- EASY TO INSTALL
- EASY TO USE
- NO POWER REQUIRED
- AUTOMATIC DEMAND BASED REGENERATION
- CONTINUOUS UNINTERRUPTED SOFT WATER
- USES LESS WATER
- USES LESS SALT
- BYPASS VALVE
- 2 YEAR WARRANTY*



The Delta Ontario can soften up to 2,000 litres per hour of water. Regenerating automatically as required, using 100 litres of water and 2.4kgs of salt. For larger flow rates and capacities, simply connect more units in parallel. Max pressure 8 bar.

APPLICATIONS:

Domestic, production plants, sports facilities, reverse osmosis pre-treatment, package boilers and cooling tower feed.

MODELS:

Model Code	Capacity	Operating Range
ONTARIO 1x12L	600ppm/m ³	200-600 ppm Hardness
ONTARIO 2	1200ppm/m ³	

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.

DELTA MULTIPLE WATER SOFTENERS

For all the advantages of the Delta softeners with larger capacities, Delta assemble multiple dual water softeners in parallel.



Further information on request.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.