

EMEC DIN DIGITAL SERIES DIN RAIL MOUNTED CONTROLLER

STANDARD FEATURES:

- DIN RAIL MOUNTING MEASURING INSTRUMENT
- BACKLIT LCD DISPLAY
- TWO ON/OFF OR PWM CONTROL RELAYS
- FLOW ALARM
- 4-20mA OUTPUT FOR MEASURED VALUE
- PROBES SUPPLIED SEPARATELY
- 2 YEAR WARRANTY*



MODELS:

| Model | Function |
|------------------------------|--|
| DIN DIGITAL PH | Digital pH meter (from 0-14 pH). Automatic temperature compensation, two on/off or PWM (pulse width modulated) set-points, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL RH | Digital Redox (ORP) meter (0-1000 mV). Two on/off or PWM set-points, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL CL | Digital Chlorine meter (Total chlorine, free chlorine, hydrogen peroxide, bromine, peracetic acid). Two on/off or PWM set-points, flow alarm, 4-20mA output signal proportional to read value. |
| DIN DIGITAL CD | Digital conductivity control (0-20, 0-200, 0-2000µS, 0-20, 0-200mS). Automatic temperature compensation, with two on/off or PWM set-points, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL O ₃ | Digital Ozone Controller (0-1mg/l or 0-10mg/l), with two on/off or PWM set-points, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL O ₂ | Dissolved Oxygen Controller (0-60 mg/l), with two on/off or PWM set-points, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL CLO ₂ | Digital Chlorine Dioxide Controller (0-2 or 0-20mg/l), with two on/off or PWM set-points, a flow alarm, and a 4-20mA output signal proportional to read value. |
| DIN DIGITAL TEMP | Digital Temperature Controller (0-100 degrees C), with two on/off or PWM set-points, and a 4-20mA output signal proportional to read value. |

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.