

EMEC INJECTION LANCES

The injection lance allows the injection fitting to be withdrawn, serviced and refitted without depressurising the process line.



PART CODE	DESCRIPTION	PART CODE	DESCRIPTION
LINI-V	1/2+Injection Lance PVDF / Viton	LINIR-V	LINI-V with PVC ball valve
		LINIR-K	LINI-V with PVDF ball valve
LINI-D	1/2+Injection Lance PP / EPDM	LINIR-D	LINI-D with PVC ball valve

PVDF rated for 100°C at 8 Bar. PP rated at 40°C at 8 Bar. Extensions available 5,10 and 15cm long
Available in a range of pipe connections, see page 8. Specify when ordering.

EMEC SUCTION LANCES



EMEC RIGID SUCTION LANCE, WITH ADJUSTABLE HEIGHT, FOOT VALVE AND FLOAT SWITCH BUILT IN	
DESCRIPTION	PART CODE
EMEC rigid suction lance, 4 x 6, 1/2+, PVC, Viton seals, available in 40, 63, 75, 108 and 122cm lengths	LASP4/V
EMEC rigid suction lance, 4 x 6, 1/2+, PVC, EPDM seals, available in 40, 63, 75, 108 and 122cm lengths	LASP4/D
EMEC rigid suction lance, 6 x 8 (or 8 x 12), 1/2+, PVC, Viton seals, available in 40, 63, 75, 108 and 122cm lengths	LASP5/V
EMEC rigid suction lance, 6 x 8 (or 8 x 12), 1/2+, PVC, EPDM seals, available in 40, 63, 75, 108, & 122cm lengths	LASP5/D

OPTIONS: Available with double suction connections for two pumps, LASP4 available with double float switches. Specify distance when ordering.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.