

ARGAL TMA SELF PRIMING CHEMICAL PUMPS

FEATURES:

- SELF PRIMING PUMP- UPTO . 5M SUCTION LIFT
- IEC STANDARD MOTORS
- MAGNETICALLY COUPLED CENTRIFUGAL PUMPS
- NO METAL SHAFT OR MECHANICAL SEAL
- ALL THERMOPLASTIC (GFR/PP OR CFF/E-CTFE) BODY & IMPELLOR FOR SUPERIOR CHEMICAL RESISTANCE
- 12 MONTH WARRANTY*



PUMP MODELS:

Model	Max Head (m)	Max Capacity L/min	Connections
TMA 0116	22	40	3/4+BSP
TMA 1014	20	266	1 1/2+BSP

OPTIONS:

Motor	Single Phase, Three Phase, Assorted IP Ratings
Pump Head Available In	GFR/PP or CFF/E-CTFE
3 Versions	N, P or S for High SG Liquids (1.05, 1,35 and 1.8 respectively)
Impellor Shaft	CER or SiC
Bushes	CARB/HD, SiC or GFR/PTFE
O-Ring Gasket	EPDM or Viton

Explosion Proof Version Available.

NOTE: Abrasive chemicals will reduce the life of the pump.

* Please refer to Aqua Products Limited terms and conditions of sale for complete warranty conditions.