

SECTION 9

AODD Pumps

9

ASTRA EVO

Air Operated Double Diaphragm Pumps

Standard Features:

- Self Priming
- Submersible or Dry Mount
- Variable Flow Rates & Discharge Pressures
- Dead Head without Damage
- Run Dry without Damage
- High Solids Handling
- Viscous Liquids Handling
- Corrosive Liquids Handling
- Gentle on Shear Sensitive Fluids
- 12 Month Warranty*

ARGAL
PUMPS



BEST IN CLASS
Low Air Consumption

Sizes:

Model	Max Head m	Max Capacity l/m	Connections Inch BSP	Max Solids Size mm
DDE 30	80	52	1/2	3.5
DDE 60	80	76	1/2	3.5
DDE 100	80	130	1	3.5
DDE 160	80	175	1	7.5
DDE 400	80	370	1-1/2	8.5
DDE 650	80	715	2	8.5

Options:

Connections	BSP standard. NPT or Flanged on request
Pump Case Material	PP, PVDF, Aluminium, 316SS
Diaphragms	Keyflex, Santoprene PTFE
Balls	EPDM, NBR, PTFE, 316SS
Ball Seats	PVDF, 316SS, PP, UPPE
O-Rings	EPDM, Viton, NBR, PTFE
Hazardous Areas	ATEX Zone 1 Rated Versions

Applications:

Wastewater, chemicals, oils, ink, paint, industrial washing & de-greasing, drum transfer, sand slurries, cleaning products, solvents, lacquers, chemical transfer, sump pump.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.