

SECTION 11

Chlorine Dioxide Generators

LOTUS ULTRA

Chlorine Dioxide Generator

Standard Features:

- Sodium Chlorite/Hydrochloric Acid Method
- Instantaneous ClO_2 Production
- Dosing Proportional to Flow or Residual Set-Point
- Flow Control Input
- Tank Level Alarms
- Real Time Production Data
- Pump and Flow sensor Monitoring
- Water Meter Input
- Standby Input
- Internal Data Logging
- 4-20mA Output
- Service Reminder
- Colour Coded Pumps
- 2 Year Warranty*

Models:

Model	Pressure Bar	Capacity g/h
LOTUS ULTRA 1	5	1000
LOTUS ULTRA 2	5	2000
LOTUS ULTRA 3	5	3000
LOTUS ULTRA 4	5	4000

Versions:

	Standard version
ERH	Built-in redox measurement
SCL2	Built-in chlorine dioxide measurement
SCL17	Built-in chlorine dioxide measurement (high pressure or high temperature)

Options:

Ethernet connection, GPRS option, data logging to USB, remote control via the ERMES Web Server, MODBUS, WIFI, GAS detector option.

Applications Include:

Food and beverage manufacturing, bottle washing, potable water, process water, produce washing, cooling towers and swimming pools.



* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.