

SECTION 26

Pipe Fittings

26

UPVC Schedule 80 Pipe Fittings

Standard Features:

- Schedule 80 PVC Fittings
- American Pipe Standard
- Manufactured in Grey UPVC
- Superior Strength & UV Stabilised
- Operating Pressure 10 Bar
- Operating Temperature <50°C

Often used in water treatment plant rooms and assemblies for a high strength, durable & attractive finish.
Suitable for most chemicals.
Check compatibility with specific chemicals before use.

Straight Couplers

| Model | Material | Description | Size inch | Type |
|-----------------|----------|------------------|-----------|------|
| SCH80 CPL 1/2 | UPVC | Straight Coupler | 1/2 | SxS |
| SCH80 CPL 3/4 | UPVC | Straight Coupler | 3/4 | SxS |
| SCH80 CPL 1 | UPVC | Straight Coupler | 1 | SxS |
| SCH80 CPL 1-1/4 | UPVC | Straight Coupler | 1-1/4 | SxS |
| SCH80 CPL 1-1/2 | UPVC | Straight Coupler | 1-1/2 | SxS |
| SCH80 CPL 2 | UPVC | Straight Coupler | 2 | SxS |



* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.