### **SECTION 12**

Water Softeners



09 281 1865 • sales@aquasales.co.nz • www.aquasales.co.nz

12

# **DELTA HYDROSOFT 100M**

Water Softener

### **Standard Features:**

- Ultra Compact
- · Easy to Install
- Easy to Use
- No Power Required
- No Assembly Required
- No Programming Required
- · Automatic Demand Based Regeneration
- Uses Less Water
- Uses Less Salt
- · Bypass Valve
- 2 Year Warranty\*





The amazing **DELTA HYDROSOFT 100M** water softener sets a new standard for efficiency and performance.

It outperforms traditional water softeners, and yet it is small enough to fit under a sink bench.

The softener sits inside the brine tank for a compact tidy finish.

Regenerating automatically as required, the DELTA HYDROSOFT 100M regenerates in just 15 minutes, using only 18L of water and 0.3kgs of salt.

### Models:

Model	Flow Rate I/h	Connections inch	Capacity ppm/m3	Operating Range PPM
DHSO100M	1500	3/4	150	150 - 600

### **Dimensions:**

240mm (W) x 540mm (L) x 483mm (H)

### **Applications:**

Domestic homes, cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

Page 1 - Section 12 Catalogue 2021

<sup>\*</sup> Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.



09 281 1865 • sales@aquasales.co.nz • www.aquasales.co.nz

## **DELTA HYDROSOFT 200M DUPLEX**

Water Softener

### **Standard Features:**

- Ultra Compact
- Easy to Install
- Easy to Use
- No Power Required
- · No Assembly Required
- No Programming Required
- Automatic Demand Based Regeneration
- Continuous Uninterrupted Soft Water
- Uses Less Water
- Uses Less Salt
- · Bypass Valve
- 2 Year Warranty\*





The twin parallel configuration of the DELTA HYDROSOFT 200M Duplex water softener provides continuous uninterrupted soft water with easy salt refill.

Staggered regeneration ensures continuous soft water.

Each softener regenerates in just 15 minutes, using only 18L of water and 0.3kgs of salt.

### Models:

Model	Flow Rate I/h	Connections inch	Capacity ppm/m3	Operating Range PPM
DHSO200M	2600	3/4	2 x 150	150 - 600

### **Dimensions:**

460mm (W) x 490mm (L) x 470mm (H)

### **Applications:**

Domestic use, cafés, commercial kitchens, dishwashers, dispensing machines, humidifiers, reverse osmosis pre-treatment, package boilers and cooling tower feed.

\_\_\_\_

Catalogue 2021 Page 2 - Section 12

<sup>\*</sup> Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.