

## SECTION 22

Level

### Float Switches

22

#### Standard Features:

- Polypropylene Body, Rubber Cable
- Operating Temperature 0 - 40°C
- Level of Protection IP68
- 1 Bar
- N/O & N/C
- 20 (8)A, 250VAC
- TUV, CE Approvals
- 12 Month Warranty\*



#### Models:

##### Compact General Purpose Float Switch

Model	Cable Length mtr	Dimensions mm	Buoyancy ml
Olympic3D	3	74 x 124 x 38	200
Olympic5D	5	74 x 124 x 38	200
Olympic10D	10	74 x 124 x 38	200

#### Applications:

Switching pumps, for filling or emptying, alarms or control.



#### Models:

##### Heavy Duty BMS Float Switch

Model	Cable Length metre	Dimensions mm	Buoyancy ml
A5050160	10	156 x 113 x 61	560

#### Applications:

Suitable for dirty water applications, e.g. chambers with sludge and scum.

\* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

## SECTION 22

Level

# 22 Float Weights

### Standard Features:

- Counterweight for Correct Float Operation
- Built-in Reusable Cable Lock
- 12 Month Warranty\*



### Models:

Model	Description
A5018060	Small weight, to suit Olympic floats
A5018040	Large weight, to suit BMS floats

### Option:

Model	Description
Fixing Kit	Fixing kit for floats

\* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.