

09 281 1865 • sales@aquasales.co.nz • www.aquasales.co.nz

10

## pH Probes





pH Probe Model — EPH	
Single junction epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 70°C. 12mm dia. Minimum conductivity 100μS.	
Applications	Potable water, swimming pools, laboratory use.
EPHS	0.8 meter cable and BNC connector
EPHM	4.5 meter cable and BNC connector
FPHI	15 meter cable and BNC connector



ph Probe Model — EPHM/D	
Double junction epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 70°C. 12mm dia. Minimum conductivity 100µS.	
Applications	As above plus wastewater, and medias containing proteins, silver or sulphides.
EPHM/D	4.5 meter cable and BNC connector
EPHL/D	15 meter cable and BNC connector



pH Probe Model — EPHMD/100	
Double junction epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 100°C. 12mm dia. Minimum conductivity 100µS.	
Applications	Wastewater e.g. electroplating, and medias containing proteins, silver or sulphides. Suitable for high temperature wastewater applications.
EPHMD/100	4.5 meter cable and BNC connector



pH Probe Model — EPHMD/LI	
Double junction epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 70°C. 12mm dia. Minimum conductivity 3µS.	
Applications	Low Ionic (conductivity) applications.
EPHMD/LI	4.5 meter cable and BNC connector



pH Probe Model — EPHM/HF	
Epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 70°C. 12mm dia. Minimum 100µS.	
Applications	Hydrogen fluoride resistant.
EPHM/HF	4.5 meter cable and BNC connector

Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

Page 17 - Section 10 Catalogue 2021

09 281 1865 • sales@aquasales.co.nz • www.aquasales.co.nz

## **pH Probes**



pH Probe Model — EPH SC	
Epoxy shaft pH 0-14 probe . Max. pressure 7 bar at 70°C. 12mm dia. Minimum 100μS.	
Applications	High solids wastewater, mount in flow path for self cleaning action.
EPHSC	Self cleaning, flat tip. 4.5 meter cable and BNC connector



pH Probe Model — EPH SN6 Range	
Epoxy shaft pH 0-14 probe. Max. pressure 7 bar at 70°C. 12mm dia. Minimum 100µS.	
Applications	High solids wastewater, mount in flow path for self cleaning action.
EPHSN6	PG13.5 mounting thread and SN6 connector
EPHM/D/SN6	Double junction. PG13.5 mounting thread and SN6 connector
EPHSC/SN6	Self cleaning, flat tip. PG13.5 mounting thread and SN6 connector



Accessories for ORP & pH Probe Installations	
CASN6S	BNC/SN6 cable for ERHSN6 probe, 5m
CASN6M	BNC/SN6 cable for ERHSN6 probe, 10m
CASN6L	BNC/SN6 cable for ERHSN6 probe, 15m
GHIERA	PG13.5 threading nut for ORP probes, with O-ring

Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

Catalogue 2021 Page 18 - Section 10

10