

Section 2

Solenoid Metering Pumps

EMEC F Series Metering Pumps

Standard Features:

- Stroke Rate Adjustment 0-100%
- Chemical Level Switch Input
- Housing and Liquid Ends in Polypropylene
- Level of Protection IP65
- PTFE Diaphragm
- 5 Year Warranty*



The F series metering pumps provide effective metering in a low cost wall mounting configuration. These popular units are often applied in swimming pools, cooling and heating circuits and in horticulture.

The F series pumps were superseded by the V series (see pages 15-18, section 2) over 10 years ago. However F series pumps remained so popular that EMEC continues to make them.

They have a smaller footprint than the V series, making them useful for squeezing into tight spaces.

All pumps are supplied with suction and discharge tubing, foot valve, injection valve and low level float switch. Control cables are also included where relevant.

Sizes:

Model	Pressure Bar	Flow l/h	Cc/Stroke	Valve Size BSP inch	Tube Size ID x OD
1201.5	12	1.5	0.17	3/8	4 x 6
1002.2	10	2.2	.25	3/8	4 x 6
0703	7	3	0.34	3/8	4 x 6
0505	5	5	0.56	3/8	4 x 6
0306.5	3	6.5	0.72	3/8	4 x 6

Models:

Model	Function
FCL	Manual setup with low level float switch.
FPVM	F pump with external pulse input signal, built-in pulse multipliers/dividers.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.