

FLUIMAC

Air Operated Double Diaphragm Pumps

Standard Features:

- Self Priming, Variable Flow Rates & Discharge Pressures, Dead Head without Damage, Run Dry without Damage, High Solids Handling, Viscous Liquids Handling, Corrosive Liquids Handling, Gentle on Shear Sensitive Fluids, 12 Month Warranty*

Available Models:



PHOENIX

Air Operated Double Diaphragm Pumps
Available in PP, PVDF, Aluminium, Stainless steel POMc
Flow Rates from 7lpm to 1000lpm



PHOENIX FOOD

Air Operated Double Diaphragm Pumps
Electropolished 316 Stainless steel , with Tri Clamp connections
Flow Rates from 20lpm to 1000lpm



PHOENIX ATEX

Air Operated Double Diaphragm Pumps
Certified for Zone 1 Hazardous Areas
Flow Rates from 7lpm to 1000lpm



ACCURATE PHOENIX

Air Operated Double Diaphragm Pumps
Stroke By Stroke Remote Speed Control
Flow Rates from 7lpm to 250 lpm




TWIN PHOENIX

Air Operated Double Diaphragm Pumps
Double inlet/outlet connections for equal pumping of two medias
Flow Rates from 7lpm to 700 lpm



POWDER PHOENIX

Air Operated Double Diaphragm Pumps
Special design to handle powder
Available in Aluminium, 316SS,



SUBMERSIBLE PHOENIX

Air Operated Double Diaphragm Pumps
Configured To Operate When submerged
Flow Rates from 7 to 1000 lpm.

Applications:

Wastewater, chemicals, oils, ink, paint, industrial washing & de-greasing, drum transfer, sand slurries, cleaning products, solvents, lacquers, chemical transfer, sump pump.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.