

Miscellaneous Probes

10



Temperature Probe Model — ETEP CH18

High linearity temperature probe with PVDF body, 1/2 inch thread 0-100°C, 10 Bar, 1mV=0.1°C. 4m cable.

ETEPC18	NTC10kohm sensor, ECL6 or PEF Holder
ETEPC18/L	NTC 10kohm sensor, NPED PEF22 or PEF23 Holder
ETEPTCH18	PT100 sensor, ECL6 or PEF Holder
ETEPTCH18/L	PT100 sensor, ECL6 or NPED or PEF22 or PEF23 Holder

Turbidity Sensor Model — ETORB40

Off line Turbidity Sensor, max flow 40 lph, maximum pressure 0.5 bar.

Applications	Swimming pools, potable water systems.
ETORB40	0-40 NTU

Turbidity Probe Model — ETORB2

Turbidity probe with self cleaning function (by water injection), maximum pressure 2 bar at 40°C, internal temperature compensation, 5m cable.

ETORB2	0-4000 NTU
ETORB2-IM	0-4000 NTU, 10m cable

Dissolved Oxygen Probe Model — EOLUM

Dissolved Oxygen probe with fluorescence membrane, maximum pressure 10 bar, -5-50°C, temperature compensation (PT100), 15m cable.

EOLUM	0-20 mg/l O ₂
-------	--------------------------

Fluoride Probe Model — EFL

Ion selective probe (ISE) for Fluoride (F-), maximum pressure 1 bar, 0-60°C, pH range 5-7, 1m cable.

EFL	0-3 PPM
-----	---------

Tracer Probe Model — ETRC

Tracer probe, PVC body, 4-20mA output, 0-50°C, 7 Bar, 0.8m cable.

ETRC	Dynamic range 0-300 ppb
------	-------------------------

Corrosion Probe Model — ECORR

Corrosion probe, SS body, RS485 output, 0-50°C, 7 Bar.

ECORR	Range 0.001-10MPY
-------	-------------------

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.