

Section 13

Reverse Osmosis

RO Machines

Reverse Osmosis

13

Standard Features:

- SS Frame
- Permeate Flow Meter
- Concentrate Flow Meter
- Recycle Flow Meter
- Inlet Pressure Gauge
- Operating Pressure Gauge
- Concentrate Pressure Gauge
- 2 Stage Pre Filters
- Microprocessor Control
- Conductivity Monitor
- Auto Flush System
- Manual Flush Push Button



Models:

Model	Permeate Flow l/h	Recovery Rate %	Rejection rate %	No. of Elements	Membrane Size inch	Power Consumption
RO 1500	180	50-75	95-98	1	4.0 x 40	1.5kW 1 phase
RO 3000	360	50-75	95-98	2	4.0 x 40	1.5kW 1 phase
RO 6000	725	50-75	95-98	4	4.0 x 40	2.2kW 3 phase
RO 9000	1090	50-75	95-98	6	4.0 x 40	3kW 3 phase
RO 12000	1450	50-75	95-98	8	4.0 x 40	4kW 3 phase
RO 15000	1815	50-75	95-98	10	4.0 x 40	4kW 3 phase
RO 18000	2180	50-75	95-98	12	4.0 x 40	5kW 3 phase

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.