

Section 12

Water Softeners

12

AUTOTROL

Water Softener

Standard Features:

- Fully Automatic
- Quality Components Throughout
- Autotrol 268 High Capacity Valve
- 762 Series Demand Based Regeneration
- 12 Month Warranty*



Models:

Model	Vessel Size D x H mm	Service Flow lpm	Backwash Flow lpm	Capacity Grains	Connections Inch BSP
AWS735-268-762	152 x 890	7	5	10,500	1
AWS844-268-762	200 x 1120	17	6	22,000	1
AWS1054-268-762	250 x 1380	30	9	44,000	1
AWS1252-268-762	300 x 1320	45	13	66,000	1
AWS1465-268-762	350 x 1650	70	18	88,000	1

Applications:

Domestic, industrial, food manufacturing, reverse osmosis pre-treatment, boiler feed water.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

Section 12

Water Softeners

AUTOTROL Magnum

Water Softener

12

Standard Features:

- Valve Manufactured in Noryl
- Operating Pressure 20-125 PSI
- For 4" Tank Opening
- 12 Month Warranty*



Models:

Model	Vessel Size D x H mm	Service Flow lpm	Backwash Flow lpm	Capacity Grains	Connections Inch BSP
AWS1665-298-762	400 x 1650	98	24	123,620	2
AWS2061-298-762	500 x 1550	140	37	176,600	2
AWS2472-298-762	600 x 1828	175	53	220,750	2
AWS3062-298-762	760 x 1570	280	83	353,200	2

For water softeners greater than 30 inch, a custom design is required.

Applications:

Industrial water softening, food manufacturing, boiler feed water, reverse osmosis pre-treatment.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

Section 12

Water Softeners

12

AUTOTROL Duplex

Water Softener

Standard Features:

- Twin Alternating Systems
- Fully Automatic
- Quality Components Throughout
- 764 Series Demand Based Regeneration
- 12 Month Warranty*

For high capacity applications and where continuous uninterrupted soft water is required, a DUPLEX softener is recommended.



Models:

Model	Vessel Size D x H mm	Service Flow lpm	Backwash Flow lpm	Capacity Grains	Connections Inch BSP
AWS-844-278-764	200 x 1120	17.5	6	22,075 x 2	1
AWS-1054-278-764	250 x 1370	31.6	9	39,735 x 2	1
AWS-1252-278-764	300 x 1320	45	13	57,395 x 2	1
AWS-1465-278-764	350 x 1650	70	18	88,300 x 2	1

Larger units on request.

Applications:

Industrial water softening, food manufacturing, boiler feed water, reverse osmosis pre-treatment.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

Section 12

Water Softeners

Run-Xin

Automatic Water Softener

Standard Features:

- Fully Automatic
- Demand Regeneration
- LCD display
- Adjustable Cycle Times
- Quality Components Throughout
- 12 Month Warranty*

NEW PATENTED CERAMIC DISC TECHNOLOGY

Rotating Ceramic Disks Open & Close Ports
to provide Automatic Operation.
Seal-less Design Provides Reliable Service
and Reduced Maintenance Requirements.



Models:

Model	Vessel Size D x H mm	Service Flow Lpm max	Backwash Flow lpm	Capacity Grains	Connections Inch
RX855-F82	200x1120	17.5	6	22,000	1
RX1052-F82	250x1380	30	9	44,000	1
RX1252-F82	350x1650	45	13	66,000	1

Larger units on request.

Applications:

Domestic and industrial water softening, food manufacturing, boiler feed water, reverse osmosis pre-treatment.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.