EMEC Injection Lances



The injection lance allows the injection fitting to be withdrawn, serviced and refitted without depressurising the process line.

Model	Size Inch	Tube Connection	Body	Seals	Temperature	Pressure Bar	Valve
LINI/V 1/2 4x6	1/2	4 x 6	PVDF	VITON	25°C	16	None
LINI/V 1/2 6x8	1/2	6 x 8	PVDF	VITON	25°C	16	None
LINI/V 1/2 8x10	1/2	8 x 10	PVDF	VITON	25°C	16	None
LINI/V 1/2 8x12	1/2	8 x 12	PVDF	VITON	25°C	16	None
LINI/D 1/2 4x6	1/2	4 x 6	PP	EPDM	25°C	16	None
LINI/D 1/2 6x8	1/2	6 x 8	PP	EPDM	25°C	16	None
LINI/D 1/2 8x10	1/2	8 x 10	PP	EPDM	25°C	16	None
LINI/D 1/2 8x12	1/2	8 x 12	PP	EPDM	25°C	16	None
LINIR/V 1/2 4x6	1/2	4 x 6	PVDF	VITON	25°C	16	PVC
LINIR/V 1/2 6x8	1/2	6 x 8	PVDF	VITON	25°C	16	PVC
LINIR/V 1/2 8x10	1/2	8 x 10	PVDF	VITON	25°C	16	PVC
LINIR/V 1/2 8x12	1/2	8 x 12	PVDF	VITON	25°C	16	PVC
LINIR/D 1/2 4x6	1/2	4 x 6	PP	EPDM	25°C	16	PVC
LINIR/D 1/2 6x8	1/2	6 x 8	PP	EPDM	25°C	16	PVC
LINIR/D 1/2 8x12	1/2	8 x 12	PP	EPDM	25°C	16	PVC
LINIR/K 1/2 4x6	1/2	4 x 6	PVDF	VITON	25°C	16	PVDF
LINIR/K 1/2 6x8	1/2	6 x 8	PVDF	VITON	25°C	16	PVDF
LINI-SS-D 1/2 4x6	1/2	4 x 6	316SS	EPDM	150°C	25	None
LINI-SS-V 1/2 4x6	1/2	4 x 6	316SS	VITON	200°C	25	None
LINIR/V 3/4 8x12	3/4	8 x 12	PVDF	VITON	25°C	25	PVDF
LINIR/D 3/4 8x12	3/4	8 x 12	PVDF	EPDM	25°C	25	PVDF
LINIR-SS-V 1/2 4x6	1/2	4 x 6	316SS	VITON	200°C	25	316SS

PVDF shaft extensions are available in 5,10 and 15cm lengths.
PVDF coated spring available for chlorine dioxide service.
Available with a range of tube connections.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.